



Public Joint Stock Company "AutoKrAZ"



*COMFORTABLE,
POWERFUL,
MANEUVERABLE*



SHORT LOG TRUCK

KrAZ M19.2R



KrAZ M19.2R —

● *Logging equipment includes bed with solid vertical log bunks and cab guard used to prevent the cab damage by shifting logs in case of emergency application of brake*

● *The rear wall is provided with cradle for articulating crane grapple and mounted guard to prevent truck roof from damage caused by falling logs when loading/unloading*

● *The articulating crane mounted on rear overhang allows loading/unloading both truck and trailer*

● *Integral steering*



new cabover short log truck

- **Cab:**

- *Renault Kerax;*
- *high level of comfort;*
- *excellent visibility;*
- *ease of use;*
- *smooth and quiet ride;*
- *tilt and height adjustable steering column*



- **Engine:**

- *high power and reliability;*
- *reduced specific fuel consumption;*
- *meets Euro 3, Euro 4 emissions*



KrAZ M19.2R short log truck

is designed for loading, unloading and carrying 2, 4, 6 m long logs in combination with trailer over all kinds of roads, including cobblestone, crushed-stone surfaced and earth roads.

SPECIFICATIONS:

Configuration	6x4
Curb weight, kg	14 200
- front, kg	5 080
- rear bogie, kg	9 120
GVW, kg	33 200
- front, kg	8 000
- rear bogie, kg	25 200
Payload capacity, kg	19 000
Permitted gross combination weight, kg	63 200
Turbocharged diesel engine	YaMZ-6501.10 (Euro 3)
Number of cylinders	6
Displacement, l	11,12
Power at 1900 rpm, kW (hp)	266 (362)
Maximum torque at 1900 rpm, N•m	1670
Single disk clutch	MFZ 430
9-speed manual transmission	9JS200TA
Articulating crane	OMTJI-70-02
Load moment, kNm	70
Boom reach (min/max), m	3/7,3
Maximum lifting capacity at min/max radius, kg	2 000/900
Slew angle, degrees	400
Tyres	315/80R22,5
Fuel tank, l	250
Top speed, km/h	80
Maximum gradient, %	at least 30
Turning radius, m	11,0

